



Model 1840	A	B	C	E	F	G	H	J	Measure
<b>No Heat Shield</b>	10	18	13	18	18	60	18	48	inches
Using Single Wall Pipe	254	457	330	457	457	1524	457	1219	mm.
<b>With Heat Shield</b>	10	3	10	6	6	60	18	48	inches
Using Double Wall Pipe	254	76	254	152	152	1524	457	1219	mm.

  

Model 1842	A	B	C	E	F	G	H	J	Measure
<b>No Heat Shield</b>	3	18	13	18	18	60	18	48	inches
Using Single Wall Pipe	76	457	330	457	457	1524	457	1219	mm.
<b>With Heat Shield</b>	3	3	10	6	6	60	18	48	inches
Using Double Wall Pipe	76	76	254	152	152	1524	457	1219	mm.

**G = vertical distance from cooking surface to combustibles above the stove.**

**Note:** A certified double-wall stove pipe must be used to maintain 6" clearance (dimension E) from pipe to combustibles. The approved stove pipe must extend from the chimney to the stove.

**Note:** These are factory-recommended clearances. Local, state or provincial building and fire codes take precedence and must be observed. Clearances are subject to change without notice.

When heat shield is installed, **dimensions B and F** are taken from heat shield. ("Heat shield" refers to complete stove/-pipe shield kit.) **Dimension E** is taken from outside edge of pipe.

	1840	1842-0	1842-G
<b>OVERALL DIMENSIONS</b>			
Width	35 3/4"	49 1/2"	49 1/2"
Height	67 1/4"	67 1/4"	67 1/4"
Height to Cooking Surface	35"	35"	35"
Depth including Flue Boot	36 5/8"	36 5/8"	36 5/8"
Depth without Flue Boot or Doors (door clearance for delivery)	28 1/2"	28 1/2"	28 1/2"
Assembled Weight/Shipping Weight (with skid)	428/454 lb.	450/485 lb.	465/500 lb.
Carry Weight (no doors, plates, brick, grate, cabinet, etc.)	145 lb.	160 lb.	165 lb.
<b>OVEN DIMENSIONS</b>			
Capacity		3.0 cu. ft.	
Width		18 1/4"	
Height		11 1/2"	
Depth		24 3/8"	
<b>FIREBOX</b>			
Flue Size		6"	
Capacity		1.6 cu. ft.	
Width		9 1/4"	
Height		13 1/2"	
Depth		22"	
Ideal Log Length		16" to 18"	
Secondary Air		YES	
Heat Output		30,000 to 60,000 BTU / Hr.	
Approximate Area Heated		800-1800 sq. ft.*	
<b>OTHER FEATURES AND OPTIONS</b>			
Sealed Gas Burners, 11,000 BTU Liquid Propane	N/A	N/A	2
Auto-Ignition for Gas Burners (9V Battery Powered)	N/A	N/A	YES
Overhead Warmer	Standard	Standard	Standard
Side Warmer	N/A	Standard	Standard
Fireview Door		Standard	
Colors Available		Black and Black/Bisque	
Nickel Door Frames		Optional	
Nickel Victorian Trivet		Optional	
Nickel Front Legs		Optional	
Nickel Front Skirt		Optional	
Nickel Side Skirts		Optional	
Water Jacket (side – 10 gallons/hr or rear – 5 gallons/hr)		Optional	
Heat Shield Kit		Optional	